

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION , 19 .
© COPYRIGHT 19 BY AMP INCORPORATED. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	P	F	ZONE	LTR	REVISIONS	DESCRIPTION	DATE	APPD
BD	39						RLSE PER NPR 2353, WAS 88-5870-320-1	05/08/89	-

CABLE SUPPLIED BY CUSTOMER

32.77
[1.290]

33.91
[1.335]

10.16
[.400]

STRAIN RELIEF STAPLE (1 SUPPLIED)
MATERIAL: STEEL
PLATING: BRIGHT TIN/LEAD OVER NICKEL

SPRING LATCH (2 SUPPLIED)
MATERIAL: STAINLESS STEEL

MACHINE SCREW (2 SUPPLIED)
#2-56 UNC X.250

CONNECTOR (MUST BE PURCHASED SEPARATELY)

UPPER BACKSHELL (1 SUPPLIED)
MATERIAL: ZINC
PLATING: NICKEL OVER COPPER

LOWER BACKSHELL (1 SUPPLIED)
MATERIAL: ZINC
PLATING: NICKEL OVER COPPER

- 1 .270 MAX CABLE DIA
- 2. DIMENSIONS IN BRACKETS ARE IN INCHES.

METRIC

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN INCHES - MM TOLERANCES ON: 2 PLC DEC ± - 3 PLC DEC ± 0.30 (.015) ANGLES ± -		DR 05/08/89 M. MCCAFFREY	AS SHOWN	749608-1
MATERIAL -	FINISH -	CHK 05/11/89 M.E. SHIRK	REMARKS	PART NO
		APPD 05/23/89 J. BROSCARD	AMP AMP INCORPORATED Harrisburg, Pa. 17105 NAME INDIVIDUAL KIT, 26 POSITION, REDUCED WIDTH, STRAIGHT EXIT, UNKEYED, AMPLIMITE .050 Series	
		APPD - <i>Robert White Jr. 5/24/89</i>		
		PRODUCT SPEC -	SIZE B	FSCM NO 00779
		APPLICATION SPEC -	DRAWING NO 749608	
		WEIGHT -	SCALE 2:1	SHEET 1 OF 1

CUSTOMER DRAWING